

1		2		3		4		5		6		7		8																																																																																																																												
ROHS														For reference only																																																																																																																												
A		<table><tr><td>Pin数</td><td>尺寸A</td><td>尺寸B</td></tr><tr><td>1X1</td><td>-</td><td>2.0</td></tr><tr><td>1X2</td><td>2.0</td><td>4.0</td></tr><tr><td>1X3</td><td>4.0</td><td>6.0</td></tr><tr><td>1X4</td><td>6.0</td><td>8.0</td></tr><tr><td>1X5</td><td>8.0</td><td>10.0</td></tr><tr><td>1X6</td><td>10.0</td><td>12.0</td></tr><tr><td>1X7</td><td>12.0</td><td>14.0</td></tr><tr><td>1X8</td><td>14.0</td><td>16.0</td></tr><tr><td>1X9</td><td>16.0</td><td>18.0</td></tr><tr><td>1X10</td><td>18.0</td><td>20.0</td></tr><tr><td>1X11</td><td>20.0</td><td>22.0</td></tr><tr><td>1X12</td><td>22.0</td><td>24.0</td></tr><tr><td>1X13</td><td>24.0</td><td>26.0</td></tr><tr><td>1X14</td><td>26.0</td><td>28.0</td></tr><tr><td>1X15</td><td>28.0</td><td>30.0</td></tr><tr><td>1X16</td><td>30.0</td><td>32.0</td></tr><tr><td>1X17</td><td>32.0</td><td>34.0</td></tr><tr><td>1X18</td><td>34.0</td><td>36.0</td></tr><tr><td>1X19</td><td>36.0</td><td>38.0</td></tr><tr><td>1X20</td><td>38.0</td><td>40.0</td></tr><tr><td>1X21</td><td>40.0</td><td>42.0</td></tr><tr><td>1X22</td><td>42.0</td><td>44.0</td></tr><tr><td>1X23</td><td>44.0</td><td>46.0</td></tr><tr><td>1X24</td><td>46.0</td><td>48.0</td></tr><tr><td>1X25</td><td>48.0</td><td>50.0</td></tr><tr><td>1X26</td><td>50.0</td><td>52.0</td></tr><tr><td>1X27</td><td>52.0</td><td>54.0</td></tr><tr><td>1X28</td><td>54.0</td><td>56.0</td></tr><tr><td>1X29</td><td>56.0</td><td>58.0</td></tr><tr><td>1X30</td><td>58.0</td><td>60.0</td></tr><tr><td>1X31</td><td>60.0</td><td>62.0</td></tr><tr><td>1X32</td><td>62.0</td><td>64.0</td></tr><tr><td>1X33</td><td>64.0</td><td>66.0</td></tr><tr><td>1X34</td><td>66.0</td><td>68.0</td></tr><tr><td>1X35</td><td>68.0</td><td>70.0</td></tr><tr><td>1X36</td><td>70.0</td><td>72.0</td></tr><tr><td>1X37</td><td>72.0</td><td>74.0</td></tr><tr><td>1X38</td><td>74.0</td><td>76.0</td></tr><tr><td>1X39</td><td>76.0</td><td>78.0</td></tr><tr><td>1X40</td><td>78.0</td><td>80.0</td></tr></table>												Pin数	尺寸A	尺寸B	1X1	-	2.0	1X2	2.0	4.0	1X3	4.0	6.0	1X4	6.0	8.0	1X5	8.0	10.0	1X6	10.0	12.0	1X7	12.0	14.0	1X8	14.0	16.0	1X9	16.0	18.0	1X10	18.0	20.0	1X11	20.0	22.0	1X12	22.0	24.0	1X13	24.0	26.0	1X14	26.0	28.0	1X15	28.0	30.0	1X16	30.0	32.0	1X17	32.0	34.0	1X18	34.0	36.0	1X19	36.0	38.0	1X20	38.0	40.0	1X21	40.0	42.0	1X22	42.0	44.0	1X23	44.0	46.0	1X24	46.0	48.0	1X25	48.0	50.0	1X26	50.0	52.0	1X27	52.0	54.0	1X28	54.0	56.0	1X29	56.0	58.0	1X30	58.0	60.0	1X31	60.0	62.0	1X32	62.0	64.0	1X33	64.0	66.0	1X34	66.0	68.0	1X35	68.0	70.0	1X36	70.0	72.0	1X37	72.0	74.0	1X38	74.0	76.0	1X39	76.0	78.0	1X40	78.0	80.0	B	
Pin数	尺寸A	尺寸B																																																																																																																																								
1X1	-	2.0																																																																																																																																								
1X2	2.0	4.0																																																																																																																																								
1X3	4.0	6.0																																																																																																																																								
1X4	6.0	8.0																																																																																																																																								
1X5	8.0	10.0																																																																																																																																								
1X6	10.0	12.0																																																																																																																																								
1X7	12.0	14.0																																																																																																																																								
1X8	14.0	16.0																																																																																																																																								
1X9	16.0	18.0																																																																																																																																								
1X10	18.0	20.0																																																																																																																																								
1X11	20.0	22.0																																																																																																																																								
1X12	22.0	24.0																																																																																																																																								
1X13	24.0	26.0																																																																																																																																								
1X14	26.0	28.0																																																																																																																																								
1X15	28.0	30.0																																																																																																																																								
1X16	30.0	32.0																																																																																																																																								
1X17	32.0	34.0																																																																																																																																								
1X18	34.0	36.0																																																																																																																																								
1X19	36.0	38.0																																																																																																																																								
1X20	38.0	40.0																																																																																																																																								
1X21	40.0	42.0																																																																																																																																								
1X22	42.0	44.0																																																																																																																																								
1X23	44.0	46.0																																																																																																																																								
1X24	46.0	48.0																																																																																																																																								
1X25	48.0	50.0																																																																																																																																								
1X26	50.0	52.0																																																																																																																																								
1X27	52.0	54.0																																																																																																																																								
1X28	54.0	56.0																																																																																																																																								
1X29	56.0	58.0																																																																																																																																								
1X30	58.0	60.0																																																																																																																																								
1X31	60.0	62.0																																																																																																																																								
1X32	62.0	64.0																																																																																																																																								
1X33	64.0	66.0																																																																																																																																								
1X34	66.0	68.0																																																																																																																																								
1X35	68.0	70.0																																																																																																																																								
1X36	70.0	72.0																																																																																																																																								
1X37	72.0	74.0																																																																																																																																								
1X38	74.0	76.0																																																																																																																																								
1X39	76.0	78.0																																																																																																																																								
1X40	78.0	80.0																																																																																																																																								
C														C																																																																																																																												
D														D																																																																																																																												
E														E																																																																																																																												
F														F																																																																																																																												
G		<table><tr><td colspan="2">GENERAL TOLERANCES</td><td colspan="2">SCALE: 1:1</td><td colspan="2">NAME</td><td colspan="2">DATE</td></tr><tr><td colspan="2">LINEAR</td><td colspan="2">ANGLES</td><td colspan="2">APPROVED</td><td colspan="2"></td></tr><tr><td colspan="2">0.0±0.25</td><td colspan="2">X° REF±6°</td><td colspan="2">DESIGNER</td><td colspan="2"></td></tr><tr><td colspan="2">0.00±0.15</td><td colspan="2">X° ±3°</td><td colspan="2">DRAWN</td><td colspan="2"></td></tr><tr><td colspan="2">0.000±0.08</td><td colspan="2">X° X'±2°</td><td colspan="2"></td><td colspan="2"></td></tr></table>												GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE		LINEAR		ANGLES		APPROVED				0.0±0.25		X° REF±6°		DESIGNER				0.00±0.15		X° ±3°		DRAWN				0.000±0.08		X° X'±2°						G																																																																																				
GENERAL TOLERANCES		SCALE: 1:1		NAME		DATE																																																																																																																																				
LINEAR		ANGLES		APPROVED																																																																																																																																						
0.0±0.25		X° REF±6°		DESIGNER																																																																																																																																						
0.00±0.15		X° ±3°		DRAWN																																																																																																																																						
0.000±0.08		X° X'±2°																																																																																																																																								
H		<table><tr><td colspan="2">REV.</td><td colspan="2">REVISION RECORD</td><td colspan="2">DATE</td><td colspan="2">UNIT: MM</td><td colspan="2">SIZE: A4</td><td colspan="2">0.000±0.08</td><td colspan="2">X° X'±2°</td><td colspan="2">DRAWN</td><td colspan="2">TITLE: Pitch2.00mm Pin Header, Single Plastic, Single Row, Right Angle Type</td><td colspan="2">PART. NO: KDPH-0050</td><td colspan="2">DWG. NO: ENDE0050</td><td colspan="2">REV: A0</td><td colspan="2">SHEET: 1/1</td></tr></table>												REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°		DRAWN		TITLE: Pitch2.00mm Pin Header, Single Plastic, Single Row, Right Angle Type		PART. NO: KDPH-0050		DWG. NO: ENDE0050		REV: A0		SHEET: 1/1		H																																																																																																		
REV.		REVISION RECORD		DATE		UNIT: MM		SIZE: A4		0.000±0.08		X° X'±2°		DRAWN		TITLE: Pitch2.00mm Pin Header, Single Plastic, Single Row, Right Angle Type		PART. NO: KDPH-0050		DWG. NO: ENDE0050		REV: A0		SHEET: 1/1																																																																																																																		

Specification:
Current Rating : 2AMP
Temperature Range : -40℃to+105℃
Contact Resistance : 20mΩ Max
Insulation Resistance : 1000MΩ Min
Withstanding Voltage : AC 500V
Material:
Insulator : Polyester (UL94V-0)
Standard:PBT/PA6T/LCP
Contact: Brass
Plating : Au or Sn Over 50u" Ni

Height
H=1.0mm、1.5mm、2.0mm、3.0mm

P 20 9D-XXX X X-XX-X-XXX		① Series No:		② Pitch:		③ Tail&Mounting Style:		④ No. of Pins:		⑤ Insulator Color:	
P=Pin Header		08=0.80		9D=Right Angle DIP Type		Single Row		101=1*1Pin		A:Black B:Brown C:Red	
F=Female Header		10=1.00		9S=Straight SMT Type		Double Row		201=2*1Pin		D:Orange E:Yellow F:Green	
B=Box Header		12=1.27		0B=Straight DIP Type		102=1*2Pin		202=2*2Pin		G:Blue H:Violet J:Gray	
E=Ejector Header		20=2.00		0S=Horizontal SMT Type		i i		i i		K:White P:Light Blue	
		25=2.54				140=1*40pin		240=2*40pin			
		39=3.96									
		50=5.08									
⑥ Material Type:		⑦ Plating Type:		⑧ RollS Request:		⑨ Customer Code					
A-PBT		0*-Sn-Au 1*-Ni 2*-Sn 3*-Matte-Tin 5*-Au		0:No Request							
B-PA46		0A-Sn-Au 1u" 0F-Sn-Au 10u" 5A-Au 1u"		1:RoHS							
C-PA6T		0B-Sn-Au 2u" 0G-Sn-Au 15u" 5B-Au 2u"		2:HF(Halogen Free)							
D-PA9T		0C-Sn-Au 3u" 0H-Sn-Au 30u" 5C-Au 3u"									
E-LCP		0D-Sn-Au 4u" 0I-Sn-Au 40u" i									
		0E-Sn-Au 5u" 0J-Sn-Au 50u" 5J-Au 50u"									



康 导 新 能 源

网址: www.dgconne.com 电话: 0768-85337633

邮箱: 2850175888@qq.com 传真: 0768-85382827